



Seal Storm Anti-Graffiti Sealer is a one part system that is effective on many surfaces for easy removal of graffiti. It is a water-based and environmentally friendly proprietary modified silane/siloxane and organic wax based material that acts as a sacrificial coating. This weather and U.V resistant material is water vapor permeable and can be applied in multiple coatings to increase protection and ease of removal while only slightly darkening the surface on certain substrates.

CONCRETE * BRICK * MASONRY WATERPROOFER & ANTI-GRAFFITI COATING	
CATEGORY 3 SEALER	PRODUCT BENEFITS <ul style="list-style-type: none"> ◆ Slightly Darkens Surface as Each Coating is Applied ◆ Environmentally Friendly, Low VOC ◆ 100% Water Vapor Permeable ◆ U.V. resistant ◆ Mildew and Fungus Resistant ◆ Low Odor ◆ Boiling Point 760 mm Hg: 212 F, 100 C ◆ One Part System ◆ Cost Effective ◆ Increased Protection with Each Coating
<p style="text-align: center; color: blue;">Sealed Surface</p>	

USAGE:
Seal Storm Anti-Graffiti Sealer can be used on most vertical concrete, brick, and masonry surfaces to prevent damage from salt, ice, rain, mold and mildew and most importantly graffiti.

IMPORTANT: Always do a small test pattern on the surface to be sealed in order to be sure product will seal to desired results. Surface should be free of standing water, dirt, dust, oils & other contaminants.

CAUTIONS:

- ◆ Protect all adjacent surfaces, glass, aluminum, paint films, vehicles, plant life and other non-targeted surfaces from overspray. Remove overspray immediately with soap and water. Unprotected areas and plant life should be pre-wet and continuously rinsed with water.
- ◆ Eye protection and appropriate clothing and gloves should be worn to minimize skin contact.
- ◆ Use in well-ventilated area away from sparks and open flame. Do not smoke in vicinity of application. Do not store or use near sparks or open flames.

CLEAN UP:
Do not leave behind any empty containers or equipment with leftover residue. Label appropriate containers for appropriate disposal.

COVERAGE: 25 – 125 sq ft per gal. (based on # coatings)

APPLICATION:
Application temperature range 40° - 100°F.

Shake well * Protect from freezing * Do not dilute

Vertical: Mix Well, Make sure surface is dry for 48-72 hrs. Apply by spraying, brushing or rolling. Perform a test area on the required surface(s) to determine product effectiveness and coverage rates. Best results are obtained by applying product on dry porous substrates. As a standard procedure, fresh concrete should be allowed to dry for 28 days before applying. For best results two applications are recommended with the second application applied using a wet-on-wet technique.

Note: Remove graffiti with heated pressure washing system. 4-5 Applications of sealer may decrease the need to re-apply after graffiti removal.

Disclaimer/Warranties: Neither manufacturer nor seller have any knowledge or control concerning the purchaser's use of the product. No expressed warranty is made by manufacturer or seller with respect to the results of any use of the product or container that the product comes in. No implied warranties including, but not limited to, an implied warranty of merchantability or an implied warranty of fitness for a particular purpose are made with respect to the product. User shall rely on his or her own information and tests to be determine suitability of the product for the intended use and user assumes all risk and liability resulting from use of the product. Neither manufacturer nor seller assume any liability for personal injury, loss or damage resulting from the use of the product. We do not suggest or guarantee that any hazards listed herein are the only ones which may exist. In event that the product shall prove defective, buyer's exclusive remedy shall be that the seller or manufacturer shall, upon written request of buyer, replace any quantity of the product which is proven to be defective or shall, at its option, refund the purchase price of the product upon return of the product. Manufacturer shall not be responsible for use of this product in a manner to infringe on any patent held by others.

PH: (877) 634-7325
FX: (248) 853-7643

Seal Storm Products, Inc.
Email us: info@sealstormproducts.com

FOR MORE INFO VISIT
www.sealstormproducts.com