



Seal Storm Cyclone 4 Wood Restorer was designed to clean and restore exterior wood surfaces, including decks and cedar shake roofs. Cyclone 4 will eliminate years of discoloration and biological damage on cedar, redwood, teak, pressure treated, and many other wood types. It safely cleans and restores the natural beauty of wood.

WOOD RESTORER	
CATEGORY 4 HEAVY DUTY CLEANER	PRODUCT BENEFITS <ul style="list-style-type: none"> ◆ Brings Back the Appearance of New Lumber ◆ Effective On Many Types of Wood. ◆ Water-based, Environmentally Friendly and Biodegradable. ◆ Eliminates Mold, Fungus and Other Biological Damage ◆ Easy Removal of Mill Glaze, Dirt and General Weathering ◆ Non-Flammable Liquid. ◆ Low Odor ◆ Ready to Use
<p style="text-align: center;">Before / After</p>	

<p>USAGE: Cyclone 4 Wood Restorer may be used on cedar, redwood and other types of wood. Wood Restorer will not bring back natural wood color to pressure-treated green lumber.</p> <p>IMPORTANT: May Not Work on Some Pressure Treated Wood. Always do a small test pattern on the surface to be cleaned in order to be sure product will clean to desired results without any damage to substrate.</p> <p>CAUTIONS:</p> <ul style="list-style-type: none"> ◆ Protect all adjacent surfaces, glass, aluminum, paint films, vehicles, plant life and other non-targeted surfaces from overspray. Remove overspray immediately with soap and water. Unprotected areas and plant life should be pre-wet and continuously rinsed with water. ◆ Eye protection and appropriate clothing and gloves should be worn to minimize skin contact. ◆ Wood Restorer may be slippery when applied to surfaces. Use extreme caution when using on surfaces especially roofs. Use OSHA approved safety belts and non-slip steel pegged roof shoes. ◆ May affect stability of paints, stains and clear coatings. <p>CLEAN UP: Water flush shrubbery, sidewalks, blacktop, asphalt, equipment and all adjacent surfaces immediately upon contact. Dispose of containers appropriately.</p>	<p>APPLICATION: Application temperature range 40° - 100°F.</p> <p>Shake well * Protect from freezing</p> <p>Thoroughly sweep surface to be cleaned. Apply with a brush, roller or pressure sprayer. Scrub moderately with a fiber scrub brush. Allow to stand on the surface for 5-15 mins. or as determined by test procedure. Deeper stains may require additional scrubbing and re-treatment. Use water to rinse away restorer, dirt and discoloration. For best results use pressure washer set at 500 to 1000 psi or adjust pressure accordingly to prevent damage to wood fiber. Pressure washing is more effective in removing dead wood fiber and thick moss from wood surfaces, especially cedar surfaces, than hand scrubbing and rinsing with a garden hose.</p> <p>New Decking: On smooth new decking lumber, remove mill glaze by using Cyclone 4. Rinse with a pressure washer or agitate deck with a stiff fiber scrub brush, then rinse thoroughly with a garden hose.</p> <p><small>Disclaimer/Warranties: Neither manufacturer nor seller have any knowledge or control concerning the purchaser's use of the product. No expressed warranty is made by manufacturer or seller with respect to the results of any use of the product or container that the product comes in. No implied warranties including, but not limited to, an implied warranty of merchantability or an implied warranty of fitness for a particular purpose are made with respect to the product. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from use of the product. Neither manufacturer nor seller assume any liability for personal injury, loss or damage resulting from the use of the product. We do not suggest or guarantee that any hazards listed herein are the only ones which may exist. In event that the product shall prove defective, buyer's exclusive remedy shall be that the seller or manufacturer shall, upon written request of buyer, replace any quantity of the product which is proven to be defective or shall, at its option, refund the purchase price of the product upon return of the product. Manufacturer shall not be responsible for use of this product in a manner to infringe on any patent held by others.</small></p>
---	--

<p>PH: (877) 634-7325 FX: (248) 853-7643</p>	<p>Seal Storm Products, Inc.</p> <p>Email us: info@sealstormproducts.com</p>	<p>FOR MORE INFO VISIT</p> <p>www.sealstormproducts.com</p>
--	---	---