







Seal Storm F3 Tornado Concrete & Brick Cleaner is a waterborne high performance blend of surface-active agents that will remove oil, grease and dirt residue from concrete, brick, and masonry surfaces. It penetrates the substrate, loosens oil and other contaminants and lifts them up and out. The rinsed and cleaned surface and matrix is then ready to accept sealers, paint or other coatings.

CONCRETE * BRICK * MASONRY CLEANER / DEGREASER	
CATEGORY 3 HEAVY DUTY CLEANER	PRODUCT BENEFITS <ul style="list-style-type: none"> ◆ Removes Oil, Grease and Dirt Residue From Concrete, Brick, and Masonry Surfaces. ◆ Environmentally friendly, no CFC's. Biodegradable ◆ USDA Authorized for Use in Federally Inspected Meat and Poultry Plants ◆ Non-Toxic. VOC Content Less Than 0.2 pounds/gallon or 24 grams/kg ◆ Non-Flammable – Flash Point > 200° F ◆ Ready to Use
  Oil Before / After	

<p>USAGE: F3 Tornado Concrete & Brick Cleaner can be used on all concrete and masonry surfaces that require the removal of oil, grease, dirt or other contaminants. This product may help to remove efflorescence and other stains from corrosion and exposure to the elements.</p> <p>IMPORTANT: Always do a small test pattern on the surface to be cleaned in order to be sure product will clean to desired results without any damage to substrate.</p> <p>CAUTIONS:</p> <ul style="list-style-type: none"> ◆ Protect all adjacent surfaces, glass, aluminum, paint films, vehicles, plant life and other non-targeted surfaces from overspray. Remove overspray immediately with soap and water. Unprotected areas and plant life should be pre-wet and continuously rinsed with water. ◆ Eye protection and appropriate clothing and gloves should be worn to minimize skin contact. ◆ Use in well-ventilated area. Use NIOSH approved respiratory protection in areas of high vapor concentration. <p>CLEAN UP: Do not leave behind any empty containers or equipment with residue. Label appropriate containers for appropriate disposal. Cleans up with soap and water.</p> <p>COVERAGE: 50-175 sq ft/ gal.</p>	<p>APPLICATION: Application temperature range 40° - 100°F.</p> <p>Shake well * Protect from freezing</p> <p>Using low-pressure acid-resistant sprayer with flood-jet nozzle or brush, apply sufficient material to thoroughly wet the surface. Allow product to work on surface for 15 – 30 minutes. On severe buildup, use a stiff bristle nylon brush or broom to agitate. Rinse surface with pressure washer (1500 psi or higher) and squeegee off excess water. Cycle cleaning and rinsing may be necessary on severe areas.</p>
	 <p>The 150 year old brick on the left was cleaned and restored to new condition (right)</p> 
<p><small>Disclaimer/Warranties: Neither manufacturer nor seller have any knowledge or control concerning the purchaser's use of the product. No expressed warranty is made by manufacturer or seller with respect to the results of any use of the product or container that the product comes in. No implied warranties including, but not limited to, an implied warranty of merchantability or an implied warranty of fitness for a particular purpose are made with respect to the product. User shall rely on his or her own information and tests to be determine suitability of the product for the intended use and user assumes all risk and liability resulting from use of the product. Neither manufacturer nor seller assume any liability for personal injury, loss or damage resulting from the use of the product. We do not suggest or guarantee that any hazards listed herein are the only ones which may exist. In event that the product shall prove defective, buyer's exclusive remedy shall be that the seller or manufacturer shall, upon written request of buyer, replace any quantity of the product which is proven to be defective or shall, at its option, refund the purchase price of the product upon return of the product. Manufacturer shall not be responsible for use of this product in a manner to infringe on any patent held by others.</small></p>	

<p>PH: (877) 634-7325 FX: (248) 853-7643</p>	<p>Seal Storm Products, Inc.</p> <p>Email us: info@sealstormproducts.com</p>	<p>FOR MORE INFO VISIT</p> <p>www.sealstormproducts.com</p>
--	---	---