



*Seal Storm Hurricane #1 Penetrating Sealer is a one-component, environment friendly product. It is a non-flammable, non-toxic, non-acid sealer that strengthens, densifies, and internally waterproofs porous cementitious materials such as tilt up panels, split block, and concrete. Can be used as chemical hardener and dustproofers. Waterproofs stucco, plaster, terrazzo, mortar, and most natural stones.*

CONCRETE * BRICK * MASONRY VAPOR BLOCKER / DENSIFIER / CURE & SEAL	
<b>CATEGORY</b>  <span style="font-size: 2em; color: red;">4</span> <b>SEALER DENSIFIER</b>	<p style="text-align: center; color: red;"><b>PRODUCT BENEFITS</b></p> <ul style="list-style-type: none"> <li>◆ Densifies and Strengthens Concrete, Brick, and Masonry</li> <li>◆ Environmentally Friendly</li> <li>◆ Does Not Make Surface Slippery</li> <li>◆ Increases Coating Bonding Ability</li> <li>◆ Will Not Change Substrate Color</li> <li>◆ Purges Soluble Chlorides</li> <li>◆ Resists Many Acids, Oils, Greases and Salts</li> <li>◆ Breathable Vapor Blocker</li> <li>◆ Ideal for Food Preparation Areas Where Odors And Toxic Fumes Can Be Absorbed by Food</li> <li>◆ Easy Cleanup</li> <li>◆ Ready to Use</li> <li>◆ Will Not Etch Glass</li> </ul>
<p style="text-align: center; color: blue;"><b>Sealed Surface</b></p>	

**USAGE:**  
Hurricane #1 Penetrating Sealer reduces vapor emissions for application of surface coatings such as polyurea coatings, epoxy coatings, urethane coatings, as well as carpet, floor tile, sheet vinyl and hardwood flooring materials. It chemically seals, hardens and dust-proofs interior, exterior, vertical or horizontal concrete substrates.

**IMPORTANT:** Surface should be free of standing water, dirt, dust, oils & other contaminants. Do not use latex paint over Hurricane #1 Sealer.

**CAUTIONS:**

- ◆ Protect all adjacent surfaces, glass, aluminum, paint films, vehicles, plant life and other non-targeted surfaces from overspray. Remove overspray immediately with soap and water. Unprotected areas and plant life should be pre-wet and continuously rinsed with water.
- ◆ Eye protection and appropriate clothing and gloves should be worn to minimize skin contact.
- ◆ If accidentally sprayed on glass, rinse with clear water immediately to avoid having to scrap it off later.
- ◆ Wait 24-36 hrs before painting walls or slabs.

**COVERAGE:** 150 – 200 sq ft per gal depending upon finish method and whether horizontal or vertical.

**CLEAN UP:** Rinse all equipment with warm soapy water.

**APPLICATION:** Application temperature range 45° - 100°F. For 24 hrs after application.  
**Shake well \* Protect from freezing \* Do not dilute**

**Vertical:** The surface being treated may be pre-dampened with water prior to application of the sealer. Apply from top to bottom at about using a low-pressure sprayer with about 20psi at 150-200 sq ft per gallon. Apply only as much material as the surface will readily absorb. Avoid puddling and over-application. If applying paint or other coating, spray a light mist of water over the treated area after application for best possible results.

**Horizontal:** Apply generously but avoid over-application and puddling on horizontal surfaces. Brush or broom to more porous area.

**Dry Time:** Allow 4–6 hours to dry, hose off with water

Disclaimer/Warranties: Neither manufacturer nor seller have any knowledge or control concerning the purchaser's use of the product. No expressed warranty is made by manufacturer or seller with respect to the results of any use of the product or container that the product comes in. No implied warranties including, but not limited to, an implied warranty of merchantability or an implied warranty of fitness for a particular purpose are made with respect to the product. User shall rely on his or her own information and tests to be determine suitability of the product for the intended use and user assumes all risk and liability resulting from use of the product. Neither manufacturer nor seller assume any liability for personal injury, loss or damage resulting from the use of the product. We do not suggest or guarantee that any hazards listed herein are the only ones which may exist. In event that the product shall prove defective, buyer's exclusive remedy shall be that the seller or manufacturer shall, upon written request of buyer, replace any quantity of the product which is proven to be defective or shall, at its option, refund the purchase price of the product upon return of the product. Manufacturer shall not be responsible for use of this product in a manner to infringe on any patent held by others.