



CONCRETE * BRICK * MASONRY * WOOD WATERPROOFER / DUSTPROOFER / CURE & SEAL	
CATEGORY 1 SEALER	PRODUCT BENEFITS
	<ul style="list-style-type: none"> ◆ Penetration of Absorbent Surfaces. ◆ Environmentally Friendly ◆ Water Vapor Permeable ◆ Very Little Change in Appearance (Transparent) ◆ Mildew and Fungus Resistant ◆ Low Odor ◆ Breathable ◆ Non-Flammable – Flash Point > 200° F ◆ Does Not Make Surface Slippery ◆ Provides Chemical and Salt Protection ◆ Prevents Spalling and Cracking Caused from Freeze Thaw and Ice. ◆ Cost Effective Sealer
<p style="text-align: center;">Sealed Surface</p>	

Seal Storm Typhoon #1 Sealer is a one-component penetrating water repellent which contains a proprietary reactive silane and a silicone emulsion. It is breathable and provides transparent protection over above grade concrete, masonry, aggregate, brick and stucco surfaces. It is effective against the harmful effects of water, de-icing chemicals, chloride-ion intrusion, freeze/thaw exposure, spalling, airborne pollution and mold.

<p>USAGE: Typhoon #1 Sealer can be used on most vertical and horizontal concrete, brick, and masonry surfaces to prevent damage from salt, ice, rain, mold and mildew.</p> <p>IMPORTANT: Always do a small test pattern on the surface to be sealed in order to be sure product will seal to desired results. Surface should be free of standing water, dirt, dust, oils & other contaminants.</p> <p>CAUTIONS:</p> <ul style="list-style-type: none"> ◆ Protect all adjacent surfaces, glass, aluminum, paint films, vehicles, plant life and other non-targeted surfaces from overspray. Remove overspray immediately with soap and water. Unprotected areas and plant life should be pre-wet and continuously rinsed with water. ◆ Eye protection and appropriate clothing and gloves should be worn to minimize skin contact. ◆ Use in well-ventilated area away from sparks and open flame. Do not smoke in vicinity of application. Do not store or use near sparks or open flames. <p>CLEAN UP: Do not leave behind any empty containers or equipment with leftover residue. Label appropriate containers for appropriate disposal.</p> <p>COVERAGE: 50 – 200 sq ft per gallon</p>	<p>APPLICATION: Application temperature range 40° - 100°F.</p> <p>Shake well * Protect from freezing * Do not dilute</p> <p>Vertical: Apply from top down using a low-pressure sprayer at (10-25psi) with a fan tip nozzle or a rolling with 3/8” nap. Flood surface until excess runs down 6-8” below spray or roller pattern. Wet-on-wet re-application is recommended for maximum protection</p> <p>Horizontal: Warning: Applying too much may cause surface to darken. Broom Away Excess Apply a single flood coat using sufficient material so the surface remains wet for 3 to 5 minutes. For maximum coverage, a wet-on-wet re-application within 2 minutes is recommended.</p> <p>Dry Time: 3-8 hrs depending on temp and humidity</p> <p><small>Disclaimer/Warranties: Neither manufacturer nor seller have any knowledge or control concerning the purchaser’s use of the product. No expressed warranty is made by manufacturer or seller with respect to the results of any use of the product or container that the product comes in. No implied warranties including, but not limited to, an implied warranty of merchantability or an implied warranty of fitness for a particular purpose are made with respect to the product. User shall rely on his or her own information and tests to be determine suitability of the product for the intended use and user assumes all risk and liability resulting from use of the product. Neither manufacturer nor seller assume any liability for personal injury, loss or damage resulting from the use of the product. We do not suggest or guarantee that any hazards listed herein are the only ones which may exist. In event that the product shall prove defective, buyer’s exclusive remedy shall be that the seller or manufacturer shall, upon written request of buyer, replace any quantity of the product which is proven to be defective or shall, at its option, refund the purchase price of the product upon return of the product. Manufacturer shall not be responsible for use of this product in a manner to infringe on any patent held by others.</small></p>
---	---

PH: (877) 634-7325 FX: (248) 853-7643	Seal Storm Products, Inc. Email us: info@sealstormproducts.com	FOR MORE INFO VISIT www.sealstormproducts.com
--	---	--